Technical Data



Performance you can trust

SPATTER RELEASE OIL FREE TRIGGER SPRAY

Spatter Release Oil Free has been formulated to allow easy removal of weld spatter from metal surfaces, nozzles, jigs and fixtures when the presence of oil cannot be permitted.

Features

- Does not affect any subsequent galvanising or painting operations.
- Components can be painted without degreasing.
- Will not interfere with weld formation.
- Ideal for use on stainless steel where oil based products cannot be used.

Directions for Use

Hand held spray: Hold as near upright as possible whilst spraying. Apply a thin even film from a distance of 200-250mm (8-10ins) from the surface to be treated or, in the case of nozzles, 150-200mm (6-8ins).

Fluid version: Spatter Release Oil Free Fluid can be applied by dipping, rolling or spraying.

After treatment spatter can be easily removed with a cloth or by tapping nozzles on the side of the bench.

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL ROCOL A division of TW Ltd











Technical Data



Performance you can trust

SPATTER RELEASE OIL FREE TRIGGER SPRAY

Appearance	Clear pale amber liquid
Odour	Mild
рН	6.8
Specific Gravity	1.01
Flammability	Non-flammable
Storage	0-50°C. Normal storage requirements. Do not allow
	to freeze.
Pack Sizes – Part Codes	500ml - 66070

Date: Jan-09

T +44 (0) 113 232 2600 **F** +44 (0) 113 232 2740

E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL ROCOL A division of // Ltd









