

SAFE STEP CONCRETE REPAIR COMPOUND

Page: 1

Compilation date: 31/05/2015

Revision date: 06/01/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SAFE STEP CONCRETE REPAIR COMPOUND

Product code: 42025

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Achitectural repair compound

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington Leeds West Yorkshire LS26 8BS ENGLAND Tel: +44 (0) 113 232 2700 Fax: +44 (0) 113 232 2740 Email: customer-service@rocol.com

. . . .

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1C: H314; Skin Sens. 1B: H317

Most important adverse effects: Causes severe skin burns and eye damage. May cause an allergic skin reaction.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark



Signal words: Danger

SAFE STEP CONCRETE REPAIR COMPOUND

Page: 2

Precautionary statements:	P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P302+352: IF ON SKIN: Wash with plenty of water/.
	P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CEMENT, PORTLAND, CHEMICALS

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	65997-15-1	-	Skin Sens. 1B: H317; Eye Dam. 1: H318; Skin Irrit. 2: H315	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

SAFE STEP CONCRETE REPAIR COMPOUND

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Avoid contact with water or humidity.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

SAFE STEP CONCRETE REPAIR COMPOUND

DNEL/PNEC Values DNEL / PNEC No data available. 8.2. Exposure controls Engineering measures: Ensure there is sufficient ventilation of the area. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter. Hand protection: Protective gloves. Eye protection: Safety glasses. Ensure eye bath is to hand. Skin protection: Protective clothing. Environmental: No data available Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Powder		
Colour:	Grey		
Odour:	Odourless		
Evaporation rate:	Not applicable.		
Oxidising:	No data available.		
Solubility in water:	Soluble		
Viscosity:	No data available.		
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	20	upper:	30
Flash point°C:	No data available.	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	2.0	pH:	13
VOC g/l:	Not applicable.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

SAFE STEP CONCRETE REPAIR COMPOUND

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.
Other information:	High repeated exposures to cement dust in excess of the WEL have been linked to
	rhinitis and coughing. Skin exposure has been linked to allergic (chromium) dermatitis.
	Allergic dermatitis more commonly arises through contact with wet mixture than powder.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

SAFE STEP CONCRETE REPAIR COMPOUND

		Page:	6
12.6. Other adverse effects			
Other adverse effects:	LC50 aquatic toxicity rating has not been determined. The addition of cements to water		
	will, however, cause the pH to rise and may therefore be toxic to aquatic life in		
	some circumstances.		
Section 13: Disposal conside	erations		
13.1. Waste treatment metho	ds		
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal		
	company.		
Waste code number:	17 01 01		
Disposal of packaging:	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.		
NB:	The user's attention is drawn to the possible existence of regional or national		
	regulations regarding disposal.		
Section 14: Transport inform	ation		
14.1. UN number			
UN number:	Not Classed		
14.2. UN proper shipping nar	ne		
Shipping name:	Not Classed		
14.3. Transport hazard class	(es)		
14.4. Packing group			
14.5. Environmental hazards			
Environmentally hazardous:	No Marine pollutant: No		
14.6. Special precautions for	user		
Special precautions:	No special precautions.		
Section 15: Regulatory infor	mation		
15.1. Safety, health and envir	onmental regulations/legislation specific for the substance or mixture		
Specific regulations:	Not applicable.		
15.2. Chemical Safety Assess	sment		
Section 16: Other informatio	n		
Other information			
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	2015/830.		
	Compiled in accordance with REACH.		
Phrases used in s 2 and s 3.	H314. Causes severe skin burns and eve damage		

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

SAFE STEP CONCRETE REPAIR COMPOUND

Page: 7

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.