



MD Ceramic paste

Stand: Oktober 16

Color	white
Form	pasty
Smell	slightly
Flash point	>250°C
Komponenten	high molecular oil
Thickener	ceramic additive
Density	ca. 1,29 kg/l
NLGI-factor	ca. 2
Temperature resistance	-20°C to ca. +150°C the contained solid lubricant is up to 1500°C resistant
Shelf life	10 years
Product description	
<p>MD Ceramic paste is an universally applicable fitting lubricant with extra-ordinary lubricating properties. The product protects screw connections and provides for a loose screw connection, also after a longterm influence of heat and atmospheric effects. MD Ceramic paste has water extrusive properties and protects corrosion. In the formulation are no metals like copper, nickel, molybdenum ect.</p>	
Application area	
<p>Applicable as assembling paste for all assembling applications and anti-seize paste for all parts, which are normally treated with metal containing pastes like copper pastes and alu-pastes. Also applicable as a thin film lubrication for low planning speeds, very high pressure, high wear, stickslip, oscillatory movements, vibrations and tribocorrosion. Not to use as a bearing fat.</p>	
<p>The values are average values. They serve merely for your information, but assume no warranty.</p>	

Bergheimer Str. 15 | D-53909 Zülpich | Tel. 02252/94150 | info@marston-domsel.de
www.marston-domsel.de

The information in this product has been compiled to the best of our knowledge and is intended purely for information purposes. No claims can be inferred therefrom. Before use, thorough experiments should be carried out. Our brochure represents a basis. Responsibility for possible measures to protect property and persons lies with the user. Safety data sheets on the required standard are available for all products on request.



Application area	
<ul style="list-style-type: none">○ Workshops○ Offshore○ road building○ agriculture	<ul style="list-style-type: none">○ marine○ steel industry○ tram○ chemical industry ect.
Application	
Clean the parts first if possible and apply in a thin layer. Available in automatic cartridges á 260 g.	
Packaging	Item number
12 cartridges á 260 g	MKE.K200

Bergheimer Str. 15 | D-53909 Zülpich | Tel. 02252/94150 | info@marston-domsel.de
www.marston-domsel.de

The information in this product has been compiled to the best of our knowledge and is intended purely for information purposes. No claims can be inferred therefrom. Before use, thorough experiments should be carried out. Our brochure represents a basis. Responsibility for possible measures to protect property and persons lies with the user. Safety data sheets on the required standard are available for all products on request.