



TECHLUBE-HD

HEAVY-DUTY CABLE PULLING LUBRICANT

Гель-смазка на водной основе, которая обеспечивает максимальное снижение трения при протяжке кабеля



Свойства

- Биоразлагаемая смазка на водной основе
- Покрывает силовые кабели и медные провода изолирующим слоем
- Обеспечивает максимальное снижение трения
- Совместима со всеми типами оболочки кабеля
- Оставляет смазывающую пленку
- Не "приклеивает" кабель к трубам и кабель-каналам

Соответствует и превосходит требования:

- IEEE Guide P1210/D10. "Standard test for determining compatibility of cable lubricants with wire and cable."
- Bellcore Specification "TR-NWT-002811, Issue 1, November 1993" "Generic requirements for cable placing lubricants"

PROPERTIES

Flash Point:

None

pH:

Neutral

Odor & Appearance:

Opaque viscous stringy blue gel with faint almond odor

PACKAGE

Net Contents

1 gallon (3.78 liters)

5 gallons (18.93 liters)

Part No.

61101

61105



TECHLUBE-HD

HEAVY-DUTY CABLE PULLING LUBRICANT

DIRECTIONS

Lubricant needed to install cable: Any attempt to quantify exactly the amount of lubricant that is needed on any individual installation will fall short of being accurate. In general, experience has revealed that some valid assumptions can be made. Formulas are presented that have been found to be normally acceptable. However, there are field conditions, which may require more lubricant than the formulas provide. Knowledge of specific local conditions and experience has proven to be the best judge in these cases.

Formula A: (Non-Metric, USA)

1. For plastic conduit (PVC,ABS, Polyethylene) use the following:

$$Q = 0.0013 \times L \times D$$

$$N = 0.003 \times L \times D \text{ (for prelube bags)}$$

2. For multiple concrete, clay tile, fiber cement, fiber filled, and wood conduit use the following:

$$Q = 0.0020 \times L \times D$$

$$N = 0.004 \times L \times D \text{ (for prelube bags)}$$

Q= Amount of Techlube HD needed in gallons.

N= The number of bags needed

L= The total length of the pull in feet.

D= The inside diameter of the individual conduit in inches.

Formula B: (Metric)

1. For plastic conduit (PVC,ABS, Polyethylene) use the following:

$$Q = 0.0064 \times L \times D$$

$$N = 0.004 \times L \times D \text{ (for prelube bags)}$$

2. For multiple concrete, clay tile, fiber cement, fiber filled, and wood conduit use the following:

$$Q = 0.0098 \times L \times D$$

$$N = 0.005 \times L \times D \text{ (for prelube bags)}$$

Q= Amount of Techlube HD needed in liters.

N= The number of bags needed

L= The total length of the pull in meters.

D= The inside diameter of the individual conduit in centimeters.

MATERIAL COMPATIBILITY

- Chlorinated Polyethylene
- Cross Linked Polyethylene
- Ethylene Propylene Rubber
- High Density Polyethylene
- Hypalon
- Linear Low Density Polyethylene
- Natural Rubber
- Neoprene
- PolyVinyl Chloride



LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS®, PT® and PF® are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2168 • Rev. 6/2010